

TYPICAL GAS WELL APPROACH AND DRIVEWAY  
DETAIL AND SPECIFICATIONS

(January, 2011)

- NOTES FOR APPROACH AND DRIVEWAY:
1. MAXIMUM ALLOWABLE SLOPE OF 6%, MIN. 0.5%.
  2. PROVIDE PLAN AND PROFILE INFORMATION.
  3. PROPER DRAINAGE DESIGN AND MAINTENANCE SHALL BE PROVIDED AS PER THE LATEST EFFECTIVE "DRAINAGE DESIGN MANUAL". NO LOW WATER CROSSINGS SHALL BE ALLOWED.
  4. LOCATION OF THE MUD SHAKER SHALL BE DETERMINED BY THE ENGINEER TO KEEP THE LENGTH OF THE PROPOSED DRIVEWAY TO STAY CLEAN FROM MUD AND DEBRIS AND TO REMAIN DUST FREE.
  5. ALLOWABLE ALTERNATIVES FOR DRIVEWAYS OVER 1000' SHALL INCLUDE THE FOLLOWING:
    - A. 4" MIN. (TYPE 'B' OR 'D') H.M.A.C. PLACED OVER 6" MIN. TXDOT FLEX BASE (NCTCOG SPEC. ITEM #301.5)
    - B. 8" MIN. TXDOT FLEX BASE WITH DUST CONTROL AGENT.

